

Trailer Specification Checklist

Gooseneck Check List

1.	Confirm gooseneck type	HRG	Lo	w profile HRG		
2.	Gooseneck swing radius	with	alt	ernate swing ra	dius	
3.	Gooseneck 5th wheel ht.:					
4.	Designed loaded deck ht.:					
5.	Designed loaded deck ground c	:learance:				
6.	HRG gooseneck fenders w/ braces on top & 5" up from bottom				yes	no
7.	HRG hyd. support cylinder				yes (standard)	no
8.	Gooseneck spare tire carrier				yes (option)	no
9.	HRG gooseneck power source:					
10.	List other special options:					
Deck	Check List					
7						
1.	Confirm deck type	Doole	Duan Cida Da	ale Basim D	aak Talasaanis	Doole
	Level Deck Raised Ctr		•	ck Beam D	eck Telescopio	Deck
2.	Level Deck Raised Ctr Rear deck/rear bridge connecti	ion fix	ed remov	able (RA)	·	: Deck
2.	Level Deck Raised Ctr Rear deck/rear bridge connecti Rear deck pins (RA only)	ion fix Standard o	ed remov connections	able (RA) Flush Connec	ctions	Deck
2. 3. 4.	Level Deck Raised Ctr Rear deck/rear bridge connecti Rear deck pins (RA only) Deck outside mainbeam for Ra	ion fix Standard o ised Ctr, D	ed remov connections rop Side, Bear	able (RA) Flush Connec n Deck	ctions	
2. 3. 4. 5.	Level Deck Raised Ctr Rear deck/rear bridge connecti Rear deck pins (RA only) Deck outside mainbeam for Ra Deck width is outside	ion fix Standard c ised Ctr, D de to outsid	removed remove	able (RA) Flush Connec n Deck	ctions	
2. 3. 4. 5.	Level Deck Raised Ctr Rear deck/rear bridge connecti Rear deck pins (RA only) Deck outside mainbeam for Ra Deck width is outsid Deck length (clear	ion fix Standard o ised Ctr, D de to outsid Iength is 6	ed remove connections rop Side, Bear e edge Level Downshorter)	able (RA) Flush Connec n Deck	ctions	
2. 3. 4. 5. 6.	Level Deck Raised Ctr Rear deck/rear bridge connecti Rear deck pins (RA only) Deck outside mainbeam for Ra Deck width is outsid Deck length (clear Lumber outside mainbean	ion fix Standard o ised Ctr, D de to outsid length is 6 ms only	ed remove connections rop Side, Bear e edge Level D o'' shorter) Full width	able (RA) Flush Connec n Deck eck, Raised Cent	ctions ter, Drop Side & Tel	
2. 3. 4. 5.	Level Deck Raised Ctr Rear deck/rear bridge connecti Rear deck pins (RA only) Deck outside mainbeam for Ra Deck width is outsid Deck length (clear	ion fix Standard of ised Ctr, D de to outsid length is 6 ms only r of deck, I	ed remove connections rop Side, Bear e edge Level Downshorter) Full width	able (RA) Flush Connec n Deck eck, Raised Cent	ctions ter, Drop Side & Tel	
2. 3. 4. 5. 6.	Level Deck Raised Ctr Rear deck/rear bridge connecti Rear deck pins (RA only) Deck outside mainbeam for Ra Deck width is outsid Deck length (clear Lumber outside mainbeam Recessed crossmembers at real	ion fix Standard of ised Ctr, D de to outsid length is 6 ms only r of deck, I . (10 Ga. S	ed remove connections rop Side, Bear e edge Level Downshorter) Full width	able (RA) Flush Connec n Deck eck, Raised Cent	ctions ter, Drop Side & Tel	
2. 3. 4. 5. 6. 7. 8.	Level Deck Raised Ctr Rear deck/rear bridge connecti Rear deck pins (RA only) Deck outside mainbeam for Ra Deck width is outsid Deck length (clear Lumber outside mainbeam Recessed crossmembers at reaccovered with plate.	ion fix Standard of ised Ctr, D de to outsid length is 6 ms only r of deck, I . (10 Ga. S cement /mid turn I	removed removed removed rop Side, Bear removed	able (RA) Flush Connect The Deck Teck, Raised Cent Teck crossmembers	etions er, Drop Side & Tel (last 4 Std)	escopic
2. 3. 4. 5. 6. 7. 8.	Level Deck Raised Ctr Rear deck/rear bridge connecti Rear deck pins (RA only) Deck outside mainbeam for Ra Deck width is outsid Deck length (clear Lumber outside mainbeam Recessed crossmembers at reacovered with plate. Sidebeam/side channel reinford Check for special marker lamp	ion fix Standard of ised Ctr, D de to outsid length is 6 ms only r of deck, I . (10 Ga. S cement /mid turn I andard.	ed remover connections rop Side, Bear e edge Level Description of the second se	able (RA) Flush Connect on Deck eck, Raised Cent crossmembers de of deck.	etions ter, Drop Side & Tel (last 4 Std) yes	escopic
2. 3. 4. 5. 6. 7. 8.	Level Deck Raised Ctr Rear deck/rear bridge connecti Rear deck pins (RA only) Deck outside mainbeam for Ra Deck width is outsid Deck length (clear Lumber outside mainbeam Recessed crossmembers at real covered with plate. Sidebeam/side channel reinford Check for special marker lamp, Front deck and mid turn are sta	ion fix Standard of ised Ctr, D de to outsid length is 6 ms only r of deck, I . (10 Ga. S cement /mid turn I andard.	ed remove connections rop Side, Bear e edge Level Downships suffering suffering Full width last	able (RA) Flush Connect The Deck Flush Connect	etions eer, Drop Side & Tel (last 4 Std) yes	escopic

Rear Bridge Check List

1.	Heavy Duty Bolster ends with drop sides	yes	no		
2.	OR heavy Duty Bolster Option ends flush with top of mainbeam	yes	no		
3.	Front bridge ramp with smooth plate & traction bars	yes	no		
4.	Crossmember between axles #1 and #2 recessed additionally	yes	no		
5.	Crossmember recessed between remaining axle groups	yes	no		
6.	Fenders over rear bridge (sides only) 1/4" Tread plate 3/8" tread plate None				
7.	Lash ring type, quantity, & location				
8.	Designed for existing or future east coast/west coast config.	yes	no		
9.	Rear connection ears for axle attachment/axle extension	yes	no		
10.	Standard lighting with (3) Stop/Tail/Turn				
11.	Strobe lamps and battery backup option	yes	no		
12.	Suspension type Air ride Standard Spring ride				
	Tires: 255/75R22.5 Toyo's standard				
14.	4. Tires: Specify other option with spares required.				
15.	List other special options:		_		
16.	Trailer compatibilities:		_		
Flip A	Axle Attachment Check List Axle attachment to match trailer SN				
2.	Heavy duty rear half bolster with recessed center section	yes	no		
3.	Load bearing rear light panel	yes (standard)			
4.		with			
5.	Lash ring				
	Type:				
	Quantity:				
	Location:				
6.	Designed for existing or future east coast/west coast config.	yes	no		
7.	Standard lighting with (3) lamps on each side				
8.	Strobe lamps and battery backup option yes				
9.	Axle attachment suspension type				
10.	Tires 255/75R22.5 Toyo's standard Option 275/75R22.5				
11.	Tires Specify other option with spares require	ed.			
12.	List other special options:				