

# SPREAD AXLE LOWBOY SERIES

**Talbert**<sup>®</sup>  
SINCE 1938

**55SA-LD**



# 55SA-LD



Optional 24 in. flip gooseneck extension (increasing swing radius to 132 in.) allows greater load transfer capability.




Allows users to operate as a 3+1 spread-axle with the E1Nitro™. Can also function as four axle close coupled.




With an industry-leading 18 in. loaded deck height, the 55SA-LD offers state-of-the-art load versatility.

# 55SA-LD



- Non-ground Bearing Gooseneck Design
- 108 in. Swing Radius with Connections for 24 in. Gooseneck Extension
- Hydraulic Support Cylinder (Standard)
- Front Folding / Fixed Ramps (Optional)
- 26 ft. 0 in. Deck Length
- 12 in. Swinging / Removable Outriggers
- 8 ft. 6 in. Wide Deck
- 18 in. Loaded Deck Height / 6 in. Loaded Road Clearance
- 1/4 in. Plate Bucket Well, Last 6 ft. of Deck
- High Strength 100,000 psi Minimum Yield Steel
- 2 in. Aptiong Flooring
- Two Sections Chain Storage
- Axles: 25,000 lb. Capacity
- **RIDEWELL** Suspension: Air Ride with Automatic and Talbert +3 in. / -3 in. Manual Control
- Manual Exhaust Valve
- Tires: 275/70R22.5 (H)
- Wheels: Steel Disc, Hub Piloted with Outboard Brake Drums
- Bolsters and Half Bolster on Rear Bridge
- 41 in. Mainbeam / 37 in. Bolster Height
- Boom Well in Rear Bridge
- Spring Parking Brake on Axle Two
- 4th Axle and 3+1 EINitro™ Spread Capable
- 12 Volt LED Sealed Light System
- 110,000 lb. Capacity in 10' (4) Axle Close Coupled
- 110,000 lb. Capacity in 1/2 Deck Length in 3+1 Spread Axle Configuration
- 120,000 lb. Capacity in 1/2 Deck Length (4) Axle Close Coupled
- Estimated Weight: 23,850 lbs.
- **Valspar** R-Cure 800 Red or Black Paint

## Various Options Available Upon Request. Specifications Subject To Change Without Notice.



Dealer: